

FORD LDM Localization - 功能 #2540

功能 # 2519 (已关闭): Ford_SYSR: System Requirement

Ford_SYSR : FS_REQ0020_V1 High Beam LDM standard ramping

2024-10-24 17:57 - 玉洁 金

状态:	已关闭	开始日期:	2024-11-01
优先级:	普通	计划完成日期:	2024-11-07
指派给:	涛 陆	% 完成:	100%
类别:		预期时间:	0.00 小时
目标版本:	H003_SW0007169.A001.8	耗时:	0.00 小时
描述			
The LDM shall also have the option to select a standard LDM ramping time within parameters. To do this the parameter ‘ HB_Ramping_method_cfg ’ shall be set to ‘ 1 ’ and the parameter setting of ‘ LDM_internal_standard_ramping_cfg ’ , which is configurable to immediate, 100ms, 150ms, and 200ms. ‘ HB_Ramping_method_cfg ’ is used to choose the ramping method of BCM EEL LIN BCM or LDM standard ramping. 0x00: follow BCM LIN activation, refer to REQ0018 0x01: follow LDM standard ramping method			
子任务:			
功能 # 2826: Ford_SWER_0020_0001 : High Beam LDM standard ramping			已关闭
功能 # 2827: Ford_SWER_0020_0002 : High Beam LDM standard ramping ...			已关闭
功能 # 2917: Ford_SWER_0020_0003 : HB ramping trigger mode			已关闭
相关的问题:			
关联到 功能 #2818: Ford_SWER_0018_0002 : High Beam (HB) rampin...		已关闭	2024-11-01 2024-11-07
关联到 功能 #2952: Ford_SWER_0018_0004 : High Beam (HB) BCM EEL...		已关闭	2024-11-01 2024-11-07

历史记录

#1 - 2024-10-25 09:36 - 涛 陆

完成

#2 - 2024-10-31 15:20 - 玉洁 金

- 关联到 功能 #2818: Ford_SWER_0018_0002 : High Beam (HB) ramping accuracy and frequency 已添加

#3 - 2024-10-31 15:21 - 玉洁 金

- 关联到 功能 #2952: Ford_SWER_0018_0004 : High Beam (HB) BCM EEL LIN ramping 已添加

#4 - 2024-11-18 13:35 - 斌 徐

- 状态 从 新建 变更为 已关闭