

FORD LDM Localization - 功能 #2596

功能 # 2519 (已关闭): Ford_SYSR: System Requirement

Ford_SYSR : FS_REQ0075_V1 Configuration Support

2024-10-24 19:56 - 玉洁 金

状态:	已关闭	开始日期:	2024-10-29
优先级:	普通	计划完成日期:	2024-10-31
指派给:	槐 杨	% 完成:	100%
类别:		预期时间:	0.00 小时
目标版本:	H003_SW0007169.A001.8	耗时:	0.00 小时
描述			
BCM will support configuration of the LIN nodes using the established methods for configuration that are already in place: Method 3 to load Config Data for all supported application variants and Method 2 to select the desired variant. DTCs for Not Configured.			
The LF_EEL and RF_EEL will be configured together (Both get the same data) and the EX_EEL (FCM) is configured independently. (2x Method 2 ' s)			
The HCM will also support LIN node configuration on each of its private LIN0 and LIN1 connections to the LDM.			
Upon completion of a configuration cycle the LDM will require a complete power cycle (all power inputs to 0V for at least 1 second) in order to adopt the updated configuration.			
子任务:			
功能 # 2888: Ford_SWER_0075_0001 : BCM supprot 2 different data co...			已关闭
功能 # 2891: Ford_SWER_0075_0002 : Left and Right LDM Node configu...			已关闭
功能 # 2893: Ford_SWER_0075_0003 : HCM LIN node Configuration			已关闭

历史记录

#1 - 2024-10-25 10:45 - 涛 陆

BCM LIN功能完成

#2 - 2024-11-22 09:40 - 斌 徐

- 状态 从 新建 变更为 已关闭