

FORD LDM Localization - 功能 #2646

功能 # 2519 (已关闭): Ford_SYSR: System Requirement

功能 # 2534 (已关闭): Ford_SYSR : FS_REQ0014_V1 Low Side Driver 1 and 2 Channel Configuration

Ford_SWER_0014_0001 : Low Side Driver 1 and 2 Channel Configuration(Dataset Cfg)

2024-10-27 15:34 - 培源 左

状态:	已关闭	开始日期:	2024-10-25
优先级:	普通	计划完成日期:	2024-10-31
指派给:	培源 左	% 完成:	100%
类别:		预期时间:	0.00 小时
目标版本:	H003_SW0007169.A001.8	耗时:	0.00 小时
描述			
Dataset需要通过 “ LSD1/2_channel_assignment_cfg ” 配置项，来配置LSD连接到哪个通道或者不启用，并生成以下对应数据。 (The Dataset uses the LSD1/2_channel_assignment_cfg configuration item to configure or disable the channel to which the LSD is connected, and generates the following data.) 0x00h: Not used 0x01h: Channel 1 0x02h: Channel 2 0x03h: Channel 3 0x04h: Channel 4			

历史记录

#1 - 2024-10-29 09:26 - 培源 左
- 计划完成日期 被设置为 2024-10-31
- 状态从 新建 变更为 已解决
- % 完成 从 0 变更为 100
#2 - 2024-10-29 09:27 - 培源 左
- 主题从 Ford_SWER_0014_0001 : Low Side Driver 1 and 2 Channel Configuration(Dataset) 变更为 Ford_SWER_0014_0001 : Low Side Driver 1 and 2 Channel Configuration(Dataset Cfg)
#3 - 2024-11-01 18:29 - 斌 徐
- 状态从 已解决 变更为 已关闭