

FORD LDM Localization - 功能 #2762

功能 # 2519 (已关闭): Ford_SYSR: System Requirement
功能 # 2563 (已关闭): Ford_SYSR : FS_REQ0043_V2 Bin Class Current Setting

Ford_SWER_0043_0002 : Bin Resistor Sample For App

2024-10-29 05:19 - 涛 陆

状态:	已关闭	开始日期:	2024-11-01
优先级:	普通	计划完成日期:	2024-11-07
指派给:	云浩 汪	% 完成:	100%
类别:		预期时间:	0.00 小时
目标版本:	H003_SW0007169.A001.8	耗时:	0.00 小时
描述			
App should sample the RBIN value and convert to the resistor. Option1:the BIN resistor is in one of the BIN range The RBIN current should be used.Software shoule compare the RBIN current with the NVM BIN.The BIN current is different from the value in NVM, software should store the new RBIN current in NVM to replace the previous value. Option2:the BIN resistor is out of all the BIN range 1)The NVM current is invalid.Software should use the minimum current of the channel. And set BIN error via LIN. 1)The NVM current is valid.Software should use the NVM current of the channel. And set BIN error via LIN.			

历史记录

#1 - 2024-10-29 14:02 - 涛 陆

- 指派给 被设置为 涛 陆

#2 - 2024-10-31 17:03 - 斌 徐

- 计划完成日期 被设置为 2024-10-31

- 状态 从 新建 变更为 已解决

- 指派给 从 涛 陆 变更为 云浩 汪

- % 完成 从 0 变更为 100

编写测试用例

#3 - 2024-11-04 13:49 - 斌 徐

- 计划完成日期 从 2024-10-31 变更为 2024-11-07

- 开始日期 从 2024-10-29 变更为 2024-11-01

#4 - 2024-11-19 10:38 - 斌 徐

- 状态 从 已解决 变更为 已关闭