

FORD LDM Localization - 功能 #2952

功能 # 2519 (已关闭): Ford_SYSR: System Requirement

功能 # 2538 (已关闭): Ford_SYSR : FS_REQ0018_V1 High Beam (HB) BCM EEL LIN Activation

Ford_SWER_0018_0004 : High Beam (HB) BCM EEL LIN ramping

2024-10-30 15:50 - 玉洁 金

状态:	已关闭	开始日期:	2024-11-01																
优先级:	普通	计划完成日期:	2024-11-07																
指派给:	云浩 汪	% 完成:	100%																
类别:		预期时间:	0.00 小时																
目标版本:	H003_SW0007169.A001.8	耗时:	0.00 小时																
描述 If the value of 'HB-Ramping_method_cfg' in the configuration is selected as BCM EEL LIN BCM,the fade speed will be issued by LIN command ' LDM_HB_RampingSpeed ' ; There are four possibilities for ' LDM_HB_RampingSpeed ' :Immediate、Fast、 Medium and Slow speed; 1、 if ' LDM_HB_RampingSpeed ' = Immediate,HB immediately activate/deactivate; 2、 if ' LDM_HB_RampingSpeed ' = Fast , it will read the fade time(' HB_fade_fast_spd_cfg ') configured in the dataset; 3、 if ' LDM_HB_RampingSpeed ' = Medium , it will read the fade time(' HB_fade_med_spd_cfg ') configured in the dataset; 4、 if ' LDM_HB_RampingSpeed ' = slow , it will read the fade time(' HB_fade_slow_spd_cfg ') configured in the dataset; The list of fade times is below: 0x00= 100mS fading time 0x01= 200mS fading time 0x02= 300mS fading time 0x03= 400mS fading time 0x04= 500mS fading time 0x05= 600mS fading time 0x06= 800mS fading time 0x07= 1000mS fading time 0x08= 1250mS fading time 0x09= 1500mS fading time 0x0A= 1750mS fading time 0x0B= 2000mS fading time 0x0C= 2500mS fading time 0x0D= 3000mS fading time 0x0E= 3500mS fading time 0x0F= 4000mS fading time																			
相关的问题: <table><tr><td>关联到 功能 #2540: Ford_SYSR : FS_REQ0020_V1 High Beam LDM stand...</td><td>已关闭</td><td>2024-11-01</td><td>2024-11-07</td></tr><tr><td>关联到 功能 #2826: Ford_SWER_0020_0001 : High Beam LDM standard ...</td><td>已关闭</td><td>2024-11-01</td><td>2024-11-07</td></tr><tr><td>关联到 功能 #2827: Ford_SWER_0020_0002 : High Beam LDM standard ...</td><td>已关闭</td><td>2024-11-01</td><td>2024-11-07</td></tr><tr><td>关联到 功能 #2917: Ford_SWER_0020_0003 : HB ramping trigger mode</td><td>已关闭</td><td>2024-11-01</td><td>2024-11-07</td></tr></table>				关联到 功能 #2540: Ford_SYSR : FS_REQ0020_V1 High Beam LDM stand...	已关闭	2024-11-01	2024-11-07	关联到 功能 #2826: Ford_SWER_0020_0001 : High Beam LDM standard ...	已关闭	2024-11-01	2024-11-07	关联到 功能 #2827: Ford_SWER_0020_0002 : High Beam LDM standard ...	已关闭	2024-11-01	2024-11-07	关联到 功能 #2917: Ford_SWER_0020_0003 : HB ramping trigger mode	已关闭	2024-11-01	2024-11-07
关联到 功能 #2540: Ford_SYSR : FS_REQ0020_V1 High Beam LDM stand...	已关闭	2024-11-01	2024-11-07																
关联到 功能 #2826: Ford_SWER_0020_0001 : High Beam LDM standard ...	已关闭	2024-11-01	2024-11-07																
关联到 功能 #2827: Ford_SWER_0020_0002 : High Beam LDM standard ...	已关闭	2024-11-01	2024-11-07																
关联到 功能 #2917: Ford_SWER_0020_0003 : HB ramping trigger mode	已关闭	2024-11-01	2024-11-07																

历史记录

- #1 - 2024-10-30 15:52 - 玉洁 金
- ' HB_Ramping_method_cfg ' can be selected in the configuration (BCM EEL LIN BCM or LDM) refer to [#2540](#)
- #2 - 2024-10-30 16:02 - 玉洁 金
- 描述 已更新。
- #3 - 2024-10-30 16:10 - 玉洁 金
- 描述 已更新。
- #4 - 2024-10-31 13:19 - 斌 徐
- 状态从 新建 变更为 已解决
- 指派给从 涛陆 变更为 云浩 汪
- % 完成从 0 变更为 100

编写测试用例

#5 - 2024-10-31 15:21 - 玉洁 金

- 关联到 功能#2540: Ford_SYSR : FS_REQ0020_V1 High Beam LDM standard ramping 已添加

#6 - 2024-10-31 15:22 - 玉洁 金

- 关联到 功能#2826: Ford_SWER_0020_0001 : High Beam LDM standard ramping 已添加

#7 - 2024-10-31 15:22 - 玉洁 金

- 关联到 功能#2827: Ford_SWER_0020_0002 : High Beam LDM standard ramping - ‘ HB_Ramping_method_cfg ’ 已添加

#8 - 2024-10-31 15:23 - 玉洁 金

- 关联到 功能#2917: Ford_SWER_0020_0003 : HB ramping trigger mode 已添加

#9 - 2024-10-31 16:13 - 玉洁 金

- 主题 从 Ford_SWER_0018_0004 : High Beam (HB) BCM EEL LIN Activation 变更为 Ford_SWER_0018_0004 : High Beam (HB) BCM EEL LIN ramping

#10 - 2024-11-01 18:49 - 斌 徐

- 计划完成日期 从 2024-10-31 变更为 2024-11-07

- 开始日期 从 2024-10-30 变更为 2024-11-01

#11 - 2024-11-18 13:32 - 斌 徐

- 状态 从 已解决 变更为 已关闭