

FORD LDM Localization - 功能 #2987

功能 # 2519 (已关闭): Ford_SYSR: System Requirement
功能 # 2980 (已关闭): Ford_SYSR : FS_REQ0018&REQ0020_V1 High Beam

Ford_SWER : FS_REQ0018&REQ0020_0005 High Beam BCM EEL LIN ramping for App

2024-10-31 17:14 - 玉洁 金

状态:	已关闭	开始日期:	2024-10-31
优先级:	普通	计划完成日期:	2024-11-07
指派给:	云浩 汪	% 完成:	100%
类别:		预期时间:	0.00 小时
目标版本:	H003_SW0007169.A001.8	耗时:	0.00 小时
描述			
If APP read the value of 'HB_Ramping_method_cfg' in the dataset is selected as BCM EEL LIN BCM ,the fade speed will be issued by LIN command ' LDM_HB_RampingSpeed ' ; There are four possibilities for ' LDM_HB_RampingSpeed ' :Immediate、Fast、 Medium and Slow speed; 1、 if ' LDM_HB_RampingSpeed ' = Immediate,HB immediately activate/deactivate; 2、 if ' LDM_HB_RampingSpeed ' = Fast , it will read the fade time(' HB_fade_fast_spd_cfg ') configured in the dataset; 3、 if ' LDM_HB_RampingSpeed ' = Medium , it will read the fade time(' HB_fade_med_spd_cfg ') configured in the dataset; 4、 if ' LDM_HB_RampingSpeed ' = slow , it will read the fade time(' HB_fade_slow_spd_cfg ') configured in the dataset;			

历史记录

- #1 - 2024-10-31 17:15 - 玉洁 金
- 描述 已更新。
- #2 - 2024-10-31 17:44 - 玉洁 金
- 主题 从 Ford_SWER : FS_REQ0018&REQ0020_0005 High Beam BCM EEL LIN ramping 变更为 Ford_SWER : FS_REQ0018&REQ0020_0005 High Beam BCM EEL LIN ramping for APP
- 描述 已更新。
- #3 - 2024-10-31 17:54 - 玉洁 金
- 主题 从 Ford_SWER : FS_REQ0018&REQ0020_0005 High Beam BCM EEL LIN ramping for APP 变更为 Ford_SWER : FS_REQ0018&REQ0020_0005 High Beam BCM EEL LIN ramping for App
- #4 - 2024-11-05 16:09 - 斌 徐
- 计划完成日期 从 2024-11-01 变更为 2024-11-07
- 状态 从 新建 变更为 已解决
- 指派给 从 涛陆 变更为 云浩 汪
- % 完成 从 0 变更为 100
- 编写测试用例
- #5 - 2024-11-25 08:44 - 斌 徐
- 状态 从 已解决 变更为 已关闭